



GlideCote™

Table & Tool Surface Sealant

Reduces sliding friction and hang-ups

Will not build-up even after several applications

Will not stain or effect finishing of wood

Contains no petroleum oils or silicone

Description

Regular maintenance of saw tables and receiving tables with GlideCote™ significantly reduces sliding friction on all metal, laminate, and plastic surfaces.

Product Benefits

- Eliminates “hang-ups” on sliding surfaces.
- Protects all tools and equipment from rust.
- Up to 30% slicker than paste wax.
- Easier and quicker to apply than paste wax.
- Lasts three times (3x) longer than paste wax.
- Perfect for table saw beds, drill presses, lathes, planers, band saws, miters, panel saws, and all hand tools.

Directions

Shake well before use.

To Prevent Clogging: After each use invert the container and spray until nozzle clears.

For Saw Tables: Clean surface with degreasing agent. Spray a thin even coat of GlideCote over entire surface, including table top slides and fences. Allow a few seconds to dry. Rub lightly with a clean, dry cloth.

For Best Results: Re-spray second coat and buff lightly. Re-apply GlideCote weekly or more frequently based upon work load.

For Tools: Spray a thin even coat over entire tool surface. Let dry. Buff to shine if desired. Re-apply as needed.



For simple how-to videos visit



Get the free mobile app at <http://gettag.mobi>